

CPS SCA2~3.6KTL-PS1/EU

Single-Phase String Inverter
2-3.6kW • 1 MPPT • 500Vdc System



Efficient

Appealing yield

- 1 MPPT with Max. Efficiency 97.3%
- Easily compatible with various PV module based on max. input current 15A per MPPT
- 150% DC/AC ratio
- Lower startup & wider MPPT voltage

Smart

Pragmatic option

- Communication interfaces [RS485/ Wi-Fi (Standard) & 4G (Optional)]
- Built-in Bluetooth and App for local and remote monitoring
- Support zero export by meter

Safe

Solid quality

- Durable and robust component
- IP65 &C5 protection
- Type II SPD for both DC and AC

Model Name	CPS SCA2KTL-PS1/EU	CPS SCA3KTL-PS1/EU	CPS SCA3.6KTL-PS1/EU
DC Input			
Max. DC Voltage		500Vdc	
MPPT Operating Voltage Range		50-490Vdc	
Start Voltage		70Vdc	
Rated DC Voltage		360Vdc	
Number of MPPT		1	
Number of DC Connection Sets per MPPT		1	
Max. input current per MPPT		15A	
Max. DC short-circuit current per MPPT		20A	
String Fuse		/	
DC Disconnection Type		Integrated Switch	
AC Output			
Rated AC Power	2kW	3kW	3.6kW
Max. AC Power	2.2kVA	3.3kVA	3.6kVA
Rated AC Voltage	220/230V		
AC Voltage Range ¹	160 - 300V		
Grid Connection Type	L/N/PE		
Max. AC Current	10A	15A	16A
Grid Frequency	50/60Hz		
Grid Frequency Range ¹	45-55/55-65Hz		
Power Factor ($\cos\phi$)	>0.99(± 0.8 adjustable)		
Current THD	< 3%		
AC Disconnection Type	/		
System Data			
Topology		Transformerless	
Max. Efficiency	97.3%	97.3%	97.3%
Euro Efficiency	95.9%	96.3%	96.5%
Consumption at Night		< 1W	
Protection			
DC reverse connection protection		Yes	
AC short circuit protection		Yes	
Leakage current protection		Yes	
Grid monitoring		Yes	
Ground fault monitoring		Yes	
Surge Protection		DC Type II / AC Type II	
AFCI		Option	
Environment Data			
Ingress Protection		IP65	
Cooling Method		Natural Convection	
Operating Temperature		-25°C to +60°C	
Ambient Humidity		0 - 100%	
Altitude		4000m	
Display and Communication			
Display		LED + APP(Bluetooth)	
Communication		RS485/Wi-Fi (Standard) & 4G (Optional)	
Mechanical Data			
Dimensions (W*H*D)		320 * 344 * 137mm	
Weight		6.5kg	
DC Connection Type		MC4 (Max. 6mm ²)	
AC Connection Type		Plug and play connector	
Safety			
Certifications ²		EN 61000-6, EN/IEC 62109, IEC 61727, IEC 62116, VDE 4105, CEI 0-21, EN50549-1, VDE0126-1-1, NTS type A, UNE 217002, RD 647, UNE 217001, INMETRO PORTARIA N° 140, AS4777.2	

¹ AC Power is different under different rated AC voltage.

² The certificates are for reference only. Please consult the local sales staff for detailed certification.