

# SCH333/350K-T-EU

## Three-Phase String Inverter

333/350kW • 15 MPPTs • 1500Vdc System



## Efficient

### Higher power generation

- 15 MPPTs with Max. Efficiency 99.0%
- Max. input current 20A per string, compatible with 700Wp+ module
- Superb temperature performance, full power at 45°C
- 150% DC/AC ratio

## Smart

### Fully controllable

- Comprehensive range of communication interfaces [PLC / Wi-Fi / RS485(Standard) & 4G / Ethernet(Optional)]
- Q at night (SVG) function
- Smart string monitoring based on I-V curve scanning and diagnosis

## Safe

### Superb quality with rapid response

- Durable and robust component
- Artfully designed air forced cooling system
- IP66&C5 protection
- Type II SPD for both DC and AC
- Full range of grid monitoring and protection
- Built-in anti-PID and PID recovery function
- Smart DC controllable switch, fast and automatic fault breaking

Model Name	SCH333K-T-EU	SCH350K-T-EU
DC Input		
Max. DC Voltage	1500Vdc	1500Vdc
MPPT Operating Voltage Range	500 - 1500Vdc	500 - 1500Vdc
Start Voltage	550Vdc	550Vdc
Rated DC Voltage	1190Vdc	1190Vdc
Number of MPPT	15	15
Number of DC Connection Sets per MPPT	2	2
Max. input current per MPPT	40A	40A
Max. DC short-circuit current per MPPT	60A	60A
DC Disconnection Type	Integrated Switch	Integrated Switch
AC Output		
Rated AC Power	333kW	350kW
Max. AC Power	333kVA	350kVA
Rated AC Voltage	800V	800V
AC Voltage Range*	680 - 880V	680 - 880V
Grid Connection Type	3 / N / PE	3 / N / PE
Max. AC Current	241A	253A
Grid Frequency	50 / 60Hz	50 / 60Hz
Grid Frequency Range	45-55 / 55-65Hz	45-55 / 55-65Hz
Power Factor ( $\cos\phi$ )	>0.99( $\pm 0.8$ adjustable)	>0.99( $\pm 0.8$ adjustable)
Current THD	< 3%	< 3%
System Data		
Topology	Transformerless	Transformerless
Max. Efficiency	99.0%	99.0%
Euro Efficiency	98.8%	98.8%
Protection		
Anti-islanding Protection	Yes	Yes
DC reverse polarity protection	Yes	Yes
DC overvoltage protection	Yes	Yes
Insulation resistance detection	Yes	Yes
Residual Current Monitoring Unit	Yes	Yes
Ground fault monitoring	Yes	Yes
Surge Protection	DC Type II / AC Type II	DC Type II / AC Type II
AC short circuit protection	Yes	Yes
AC overvoltage protection	Yes	Yes
Overheat protection	Yes	Yes
PV string monitoring	Yes	Yes
I-V curve scan&diagnosis	Yes	Yes
PID prevent&recovery	Yes	Yes
Q at night	Yes	Yes
24h grid monitoring	Yes	Yes
Environment Data		
Ingress Protection	IP66	IP66
Cooling Method	Cooling Fans	Cooling Fans
Operating Temperature	-30°C to +60°C	-30°C to +60°C
Ambient Humidity	0 - 100%	0 - 100%
Altitude	4000m	4000m
Display and Communication		
Display	LED + APP(Bluetooth)	LED + APP(Bluetooth)
Communication	RS485/Ethernet/PLC/CAN	RS485/Ethernet/PLC/CAN
Mechanical Data		
Dimensions (W*H*D)	1057 * 810 * 400mm	1057 * 810 * 400mm
Weight	143kg	143kg
DC Connection Type	MC4 (Max. 6mm²)	MC4 (Max. 6mm²)
AC Connection Type	OT/DT Terminal(Max. 400mm²)	OT/DT Terminal(Max. 400mm²)

\*1 AC Power is different under different rated AC voltage.

\*2 Please consult the local sales staff for detailed certification.

\*3 For reference only. Chint Power reserve the right to alterations for the data above.