

SCH250~350K-T2-EU

Three-Phase String Inverter



Efficient

- Max. efficiency 99%, Euro efficiency 98.8%
- Supports various components 182, 210R, and 210
- Integrate anti PID and night repair functions



Safety

- 45°C rated power output, 1.1 rated power output at 40°C
- IP66 protection level and C5-M anti-corrosion level
- Intelligent DC release switch



Intelligent

- Supports maximum 400mm² wire connection, saving cable costs
- Supports PLC / RS485, saving communication cable
- Active & Reactive power control

SCH250~350K-T2-EU

Three-Phase String Inverter



Model Name	SCH250/275K-T2-EU	SCH333/350K-T2-EU
DC Input		
Max. DC Voltage	1500Vdc	
MPPT Operating Voltage Range	500 - 1500Vdc	
Start Voltage	550Vdc	
Rated DC Voltage	1190Vdc	
Number of MPPT	6	6
Number of DC Connection Sets per MPPT	5	5
Max. input current per MPPT	80A	
Max. DC short-circuit current per MPPT	125A	
String Fuse	/	
DC Disconnection Type	Integrated Switch	
AC Output		
Rated AC Power	250/275kW	333/350kW
Max. AC Power	275kVA	333/350kVA
Rated AC Voltage	800V	
AC Voltage Range*	680 - 880V	
Grid Connection Type	3Φ / PE	
Max. AC Current	198.5A	240.3/252.6A
Grid Frequency	50 / 60Hz	
Grid Frequency Range	45-55 / 55-65Hz	
Power Factor (cosφ)	>0.99(±0.8 adjustable)	
Current THD	<1%(Rated Condition)	
AC Disconnection Type	/	
System Data		
Topology	Transformerless	
Max. Efficiency	99.02%	
Euro Efficiency	98.85%	
Consumption at Night	<6W	
Protection		
DC reverse connection protection	Yes	
AC short circuit protection	Yes	
Leakage current protection	Yes	
Grid monitoring	Yes	
Ground fault monitoring	Yes	
Surge Protection	DC Type II / AC Type II	
Q at night function	Yes	
PID Prevent&Recovery	Yes	
Environment Data		
Ingress Protection	IP66	
Cooling Method	Cooling Fans	
Operating Temperature	-30° C to +60° C	
Ambient Humidity	0 - 100%	
Altitude	5000 m (>4000 m derating)	
Display and Communication		
Display	LED + APP(Bluetooth)	
Communication	RS485/PLC	
Mechanical Data		
Dimensions (W*H*D)	1120* 780 * 390mm	
Weight	127kg	
DC Connection Type	MC4	
AC Connection Type	OT/DT Terminal(Max.400 mm ²)	