

# CPS ES-6.25MW/12.5/25MWh NEW

## Utility Energy Storage System



### Key Features

- Compatible with 500+/600+Ah large cells, Battery Container energy density up 25% vs last generation.
- Standard container design for easy transport and stable delivery cycle.
- Highly integrated system minimizes on-site installation and commissioning.
- Outdoor design with high ingress protection, suitable for multiple scenarios.
- Dual-stage architecture design, enhanced HVRT stability
- Wide SCR adaption, enabling active fault ride-through.

Model Name	CPS ES-6.25MW/12.5MWh	CPS ES-6.25MW/25MWh
<b>DC Parameter</b>		
Battery Capacity	2 x 6.25MWh	4 x 6.25MWh
Rated Voltage	1331.2Vdc	
Battery Voltage Range	1164.8~1497.6Vdc	
Battery Configuration	2 x 8P416S	4 x 8P416S
<b>AC Parameter</b>		
Rated AC Output Power	6.25MW	
Medium Voltage Rating	10~35kV	
Grid Frequency	50Hz	
Vector Group	Dy1, Dy11	
Cooling Method	ONAN	
<b>System Parameter</b>		
Protection Degree	Battery Container: IP55 PCS Skid: IP54	
Cooling Method	PCS: Air Cooling Batteries :Liquid Cooling	
Operation Temperature*	-25°C ~ 55°C (> 45°C derating)	
Operating Humidity	0-95%, non-condensing	
Operating Altitude*	3000m (>2000m derating)	
Dimensions (WxHxD)	Battery Container: 6058x2896x2438mm PCS Skid: 12192x2896x2438mm	
PCS Weight	35T	35T
Battery Container Weight	2 x 48.3T	4 x 48.3T
<b>Display and Communication</b>		
Communication	Ethernet/CAN/RS485	
<b>Safety</b>		
Compliance	Battery: IEC 62619 / IEC 63056 / IEC 62477 / IEC 61000 / IEC 60730 / UL1973 / UL9540A / FCC / IEC 62620 / UL 9540 / NFPA 68 / NFPA 69 / IEC 62933-5-2 PCS: IEC 62920 / IEC 62477 / IEC 61000 / IEC 62109 / IEC 60068 / EN 50549 / UNE 217001&217002 / NTS 2.1 / AS/NZS 4777.2 / VDE 4110&4120&4130 / TOR TYPE A&B / TR3.3.1 / UL 1741 / IEEE 1547	

\* Product specifications and dimensions may be updated based on the latest information provided and are subject to change without prior notice.  
 \* Battery Container capacity shall be determined by the selected battery model.  
 \* Please consult the corresponding manufacturer for parameters related to temperature and altitude.  
 \* Final data is subject to change without prior notice.